

AERATORS

Aerators may have Motorised Rotors in the tanks which generally have gearboxes with points requiring grease lubrication.

However more modern Aerators do not have rotors but use air which is blown in at the bottom of the tanks. They do however have decanters at one end of the tanks which do require grease lubrication.

SOLUTION

Single Point 125cc gas powered automatic lubricators can be fitted directly in place of the grease nipples.

These lubricators will only need changing every 12 months and visual monitoring can be easily and quickly carried out by the operators.



125cc Mini-Luber fitted to Aerator Decanter



125cc Mini-Lubers fitted to Aerator Gearboxes



LOW COST

SIMPLE TO INSTALL

12M BETWEEN CHANGES

SLOW CONTINUOUS FEED

WELL PROVEN IN UK WWTW

ATS ELECTRO-LUBE (UK) LTD HAVE CONSIDERABLE EXPERIENCE WITH WATER INDUSTRY APPLICATIONS AND CAN OFFER FULL SITE SURVEYS AND QUOTATIONS INCLUDING INSTALLATION IF REQUIRED

ATS ELECTRO-LUBE (UK) LTD

383L JEDBURGH COURT, ELEVENTH AVENUE, TEAM VALLEY TE, GATESHEAD, NE11 0BQ
TELEPHONE: 0191 4914212 FAX: 0191 4914224 email: info@atselectrolube.co.uk